

**MGFC42V5964****5.9~6.4GHz BAND 16W INTERNALLY MATCHED GaAs FET****DESCRIPTION**

The MGFC42V5964 is an internally impedance-matched GaAs power FET especially designed for use in 5.9 ~ 6.4 GHz band amplifiers. The hermetically sealed metal-ceramic package guarantees high reliability.

**FEATURES**

- Class A operation
- Internally matched to  $50\Omega$  system
- High output power  
 $P_{1dB} = 18W$  (TYP) @ 5.9 ~ 6.4 GHz
- High power gain  
 $G_{LP} = 9$  dB (TYP) @ 5.9 ~ 6.4 GHz
- High power added efficiency  
 $\eta_{add} = 31\%$  (TYP) @ 5.9 ~ 6.4 GHz,  $P_{1dB}$
- Hermetically sealed metal-ceramic package
- Low distortion [Item: -51]  
 $IM_3 = -45$  dBc (TYP) @  $P_o = 31$  (dBm) S.C.L.

**APPLICATION**

Item -01: 5.9 ~ 6.4 GHz band power amplifier

Item -51: Digital radio communication

**QUALITY GRADE**

- IG

**ABSOLUTE MAXIMUM RATINGS** ( $T_a=25^\circ C$ )


Symbol	Parameter	Ratings	Unit
$V_{DDO}$	Gate to drain voltage	-15	V
$V_{GSO}$	Gate to source voltage	-15	V
$I_D$	Drain current	12	A
$I_{GR}$	Reverse gate current	-40	mA
$I_{GF}$	Forward gate current	84	mA
$P_T$	Total power dissipation *1	78.9	W
$T_{ch}$	Channel temperature	175	$^\circ C$
$T_{stg}$	Storage temperature	-65 ~ +175	$^\circ C$

\*1:  $T_c = 25^\circ C$

**ELECTRICAL CHARACTERISTICS** ( $T_a=25^\circ C$ )

Symbol	Parameter	Test conditions	Limits			Unit
			Min	Typ	Max	
$I_{DSS}$	Saturated drain current	$V_{DS}=3V$ , $V_{GS}=0V$	—	9	12	A
$g_m$	Transconductance	$V_{DS}=3V$ , $I_D=4.4A$	—	4	—	S
$V_{GS(off)}$	Gate to source cut-off voltage	$V_{DS}=3V$ , $I_D=80mA$	-2	-3	-4	V
$P_{1dB}$	Output power at 1dB gain compression	$V_{DS}=10V$ , $I_D=4.5A$ , $f=5.9 \sim 6.4GHz$	41.5	42.5	—	dBm
$G_{LP}$	Linear power gain		8	9	—	dB
$I_D$	Drain current		—	4.5	—	A
$\eta_{add}$	Power added efficiency		—	31	—	%
$IM_3$	3rd order IM distortion *1		-42	-45	—	dBc
$R_{th(ch-c)}$	Thermal resistance *2	$\Delta V_f$ method	—	—	1.9	$^\circ C/W$

\*1: Item-51, 2-tone test  $P_o = 31$  dBm Single Carrier Level  $f = 6.4$  GHz  $\Delta f = 10$  MHz. \*2: Channel to case

**OUTLINE DRAWING** Unit: millimeters (inches)

GF-18


**RECOMMENDED BIAS CONDITIONS**

- $V_{DS}=10V$
- $I_D=4.5A$
- $R_g=25\Omega$
- Refer to Bias Procedure


**5.9~6.4GHz BAND 16W INTERNALLY MATCHED GaAs FET**

**TYPICAL CHARACTERISTICS**


P<sub>1dB</sub>, G<sub>LP</sub> vs. f



P<sub>o</sub>, η<sub>add</sub> vs. P<sub>in</sub>



P<sub>o</sub>, IM<sub>3</sub> vs. P<sub>in</sub>



**S PARAMETERS** (T<sub>a</sub>=25°C, V<sub>DS</sub>=10V, I<sub>DS</sub>=4.5A)

f (GHz)	S Parameters (TYP.)							
	S <sub>11</sub>		S <sub>21</sub>		S <sub>12</sub>		S <sub>22</sub>	
	Magn.	Angle (deg.)	Magn.	Angle (deg.)	Magn.	Angle (deg.)	Magn.	Angle (deg.)
5.9	0.36	82	2.99	-74	0.071	-133	0.26	80
6.0	0.35	56	2.95	-91	0.071	-151	0.32	72
6.1	0.35	34	2.91	-108	0.072	-167	0.35	65
6.2	0.35	14	2.88	-124	0.078	177	0.37	58
6.3	0.34	-4	2.81	-140	0.079	161	0.41	53
6.4	0.33	-23	2.72	-157	0.079	146	0.43	48